

Turner Fluid Power Limited

Station Yard, Magor, Caldicot, Monmouthshire, NP26 3HT

Tel: 01633 881966 Fax: 01633 889385

E-mail: enquiries@turnerfluidpower.co.uk

Dunlop Hiflex SAE 100R16

Specification for R16T

Nominal Bore Size		Mean Diameter Over Wire		Maximum Diameter Over Cover		Maximum Working Pressure		Minimum Burst Pressure		Minimum Bend Radius		Approx Weight	
Inch	MM	Inch	MM	Inch	MM	PSI	Bar	PSI	Bar	Inch	MM	Lbs/ft	Kg/M
1/4	6.3	0.437	11.1	0.547	13.9	5,000	345	20,000	1379	2.00	50	0.19	0.29
5/16	8.0	0.500	12.7	0.610	15.5	4,250	293	17,000	1172	2.25	55	0.24	0.36
3/8	9.5	0.594	15.1	0.701	17.8	4,000	276	16,000	1103	2.50	65	0.30	0.44
1/2	12.7	0.720	18.3	0.827	21.0	3,500	241	14,000	965	3.50	90	0.36	0.54
5/8	15.9	0.843	21.4	0.953	24.2	2,750	190	11,000	758	4.00	100	0.42	0.63
3/4	19.0	1.000	25.4	1.106	28.1	2,250	155	9,000	620	4.75	120	0.52	0.77
1	25.4	1.311	33.3	1.417	36.0	2,000	138	8,000	552	6.00	150	0.77	1.15

Product Information

- Description** : Compact 2 wire braid hydraulic hose
: Complies with SAE 100R16
- Liner** : Black; oil resistant synthetic rubber
- Cover** : Black; oil, water, ozone & flame resistant synthetic rubber
- Reinforcement** : Two braids of high tensile steel wire
- Temperature Range** : -40°C to +100°C (-40°F TO +212°F); Intermittent use up to +125°C (257°F)*

* Petroleum based fluids only. Water based fluids at temperatures -40°C to +70°C (-40°F to +158°F)

Applications

Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

Replaces: **WR16T**

Issue	1					Drawn	Approved	Date
D&ECN	DH4368					DCR	PG	22.12.03
Date	17.09.03					MS.51.R16T.A		

