

# Turner Fluid Power Limited

Station Yard, Magor, Caldicot, Monmouthshire, NP26 3HT

Tel: 01633 881966 Fax: 01633 889385

E-mail: [enquiries@turnerfluidpower.co.uk](mailto:enquiries@turnerfluidpower.co.uk)

**HOSE TYPE :** **DH.101**

**HOSE CONSTRUCTION :**

**BARRIER:** Polyamide (PA)  
**TUBE:** Nitrile Butadiene Rubber (NBR)  
**REINFORCEMENT:** One Textile Braid (PVA)  
**COVER:** Chloroprene Rubber (Neoprene)

**TEMPERATURE RANGE:** -30<sup>0</sup> C to +110<sup>0</sup> C

(Continuing operating temperatures in excess of the specified range will shorten the life of the hose)

**CONFORMS TO:** SAE J51 Type D with regard to performance characteristics, but is dimensionally smaller.

**COMMENTS :-** Suitable for use with FREON 134a

**TYPICAL USE :-** Air Conditioning.

**BRANDING :-** Refer to MS.51.01.01, Hose Branding.

Replaces: **DH.12**

<i>ISSUE</i>	2	3	4				<i>Compiled</i>	<i>Approved</i>	<i>Date</i>
<i>D&amp;ECN</i>	DH0946	DH1069	DH1390				<b>DCR</b>	<b>DW</b>	08.03.96
<i>DATE</i>	04.07.94	20.12.94	07.03.96				<b>MS.51.101.A</b>		